Axle Work Order



	Track — (Hub Face to Hub F ————————————————————————————————————	ter				
E Company Name:		 _ Phone Number:				
Track Width: Hub face to hub face (approximately center of tire to center of tire) Spring Center Width:						
Spring Seats (check one)	Spindles (check one)	Brakes/Hub Style (check one)				
Springs under axle Springs over axle No spring seat (loose) Both	Straight4" Drop	 Bare Electric brakes Hydraulic brakes Idler Disc 				
Axle weight: $\Box 2000 \ \Box 3500 \ (2\frac{3}{8}" \ \text{Tube}) \ \Box 3500 \ (3" \ \text{Tube}) \ \Box 5200 \ / 6000 \ \Box 7000$						
Suspension Kit Style:						
Rims/Tires: Size Required:						

Bolt Pattern		Diameter (Bolt Circle)							
Stud Size (check one)	# of studs		4"	₄ 1,,	$4\frac{3}{4}$,	5 "	5 1,,	_ε 1,,	
9,			4	$4\frac{1}{2}$,	4-4	3	$5\frac{1}{2}$,	$6\frac{1}{2}$,	
⁻ 9/ ₁₆		4							
¹ / ₂		5							
₋ 5/ ₈		6							
		8							

Suspension kit? □ Yes □ No	If yes, choose style: $\ \square$ Single $\ \square$ Tandem $\ \square$ Tridem
Quanti	ty Required:

Fill out this form and fax it to us at (780) 461-3460